

H.T.H.P LUBRICANTS

Tropicalised High Performance Oil

SAE 140

H.T.H.P oil is manufactured in Belgium under european standards. It is a highly controlled oil that ensures protection of your engine to 100%.

APPLICATION

H.T.H.P SAE 140 is a mineral lubricant oil for mechanic gears and it is based on a basic oil solvent high quality with special additives for having the following features : Very strong anti-wear feeling, anti-corrosion and very good foam properties. This gear oil is used in hypoid gear for most loaded rear drive axles.


SPECIFICATION

- Standard API GL-5
- Excellent oxidation resistance
- Very good EP property
- Used for loaded rear drive axles

ANALYSIS

Density at 15°C	0.909
Viscosity at 100 °C/cSt	27.50
Viscosity index	95
TBN mg KOH/g	-
Colour	-
Viscosity at 40 °C/cSt	395.00
Viscosity at -20 °C/cP	-
Maximun Heat °C	244
Cold Point °C	-12

EXPORT (20FT CONTAINER)

1L	16500 pcs	
5L	3360 pcs	
25L	850 pcs	
205L	98 pcs	



1L.



5L.



25L.



205 L

Ensures your engine protection to 100%

www.HTHP.eu

Made in Belgium

datasheet 052016v2