

H.T.H.P LUBRICANTS

Tropicalised High Performance Oil

SAE 68

Hydraulic

H.T.H.P oil is manufactured in Belgium under european standards.

Sae 68; a high quality EP hydraulic oil, consisting of specially selected base oil refined with solvent with a natural viscosity index.

APPLICATION

HTHP Hydraulic Oil SAE 68 is suitable for heavy duty hydraulic systems as well as for low-demand differentials and bearings. This oil is also very suitable as circulation lubrication for vacuum pumps and general machine lubrication (for turbine expulsion). This oil can not be used in systems with silver parts.

SPECIFICATION

- DIN 51524-2HLP
- AFNOR NF E 48-603 HM
- ISO 11158 HM
- ASTM D 6158 HM
- excellent anti-wear characteristics
- very good anticorrosion effect
- very good oxidation stability
- very good demulsifying power
- neutral to the plastic sealings
- Denison HF-0/HF-1/HF-2
- Cincinnati Machine P-69
- Eaton Brochure 694 for 35VQ25A
- GM LS-2



1L.



5L.



25L.



205 L

ANALYSIS

Density at 15°C	0.876
Viscosity at 100 °C . mm2/s	8.70
Viscosity index	102
Viscosity at 40 °C . mm2/s	68,00
TBN mgKOH/g	0,40
Sublimation point ° C	-25
Maximun Heat °C	220
Sulfate, %	0,06

EXPORT (20FT CONTAINER)

1L	16500 pcs	
5L	3360 pcs	
25L	850 pcs	
205L	98 pcs	

A high quality EP hydraulic oil

www.HTHP.be

Made in Belgium

datasheet 112018v1