

# H.T.H.P LUBRICANTS

## Tropicalised High Performance Oil

**46**  
Hydraulic

H.T.H.P oil is manufactured in Belgium under european standards.  
It is a highly controlled oil that ensures protection of your engine to 100%.

### APPLICATION

H.T.H.P Hydraulic EP-46 high quality is specially selected from refined oil with a solvent that have a natural viscosity index and additives so to have an excellent property for anti-wear, a good oxidation stability, a very good demulsifying ability, a very good anti-foam and the release air performance. Its ultra high performance formula is neutral with respect to plastic joints and has a low point.

### SPECIFICATION

- DIN 51524-2HLP
- Suitable for heavy hydraulic systems
- Suitable in lubrication system for vacuum circulation pumps and for machines in general.

### ANALYSIS

Density at 15°C	0.872
Viscosity at 100 °C/cSt	6.97
Viscosity index	110
TBN mg KOH/g	46.00
Colour	0.40
Viscosity at 40 °C/cSt	215
Viscosity at -20 °C/cP	-30
Maximun Heat °C	215
Cold Point °C	0,06



### EXPORT (20FT CONTAINER)

1L	16500 pcs	
5L	3360 pcs	
25L	850 pcs	
205L	98 pcs	

Ensures your engine protection to 100%  
www.HTHP.be

Made in Belgium  
datasheet 022016v1